



2668EX EXPLOSION PROOF SCISSOR LIFT

SPECIFICATIONS		
Working Height	32 ft	9.8 m
Raised Platform Height	26 ft	7.9 m
Lowered Platform Height	50 in	1.3 m
Platform Size (inside)	57 x 84 in	1.4 x 2.1 m
Platform Capacity	1200 lbs	544 kg
Overall Width	68 in	1.7 m
Overall Length	118.5 in	3.01 m
Stowed Height	95.5 in	2.4 m
Deck Extension	5 ft	1.5 m
Ground Clearance (Stowed)	7.5 in	19.1 cm
Ground Clearance (Raised)	0.7 in	1.8 cm
Wheelbase	76 in	1.93 m
Inside Turning Radius	76 in	1.93 m
Outside Turning Radius	164 in	4.2 m
Drive Speed (Stowed)	1 mph	1.6 km/h
Drive Speed (Raised)	0.5 mph	0.8 km/h
Specifications Subject to Change		



SAFETY

- Explosion Proof
- Class I, Division 1, Group D
- Fully Compliant with the Latest UL 583 Type EX Standard
- ANSI A92.20 & CSA B354.6 Compliant

STANDARD EQUIPMENT

- 26 ft Platform Height
- 32 ft Working Height
- 57 x 84 in Platform Size
- 7.5 in Ground Clearance
- 1200 lb Platform Capacity
- 5 ft Extendable Deck
- Proportional Drive Controls
- Battery Condition Indicator
- Full Height Swing Gate
- Movement Alarm

OPTIONS*

- Padded Aircraft Rails
- Explosion Proof Work Lights
- 1/2" Airline to Platform
- 5 ft Powered Extension Deck

*May Change Capacity

