



A60EX EXPLOSION PROOF ARTICULATING BOOM LIFT

SPECIFICATIONS		
Working Height	66 ft	20.11 m
Platform Height	60 ft	18.47 m
Up and Over Height	26 ft 7 in	8.1 m
Platform Size (inside)	30 x 72 in	.76 x 1.83 m
Platform Capacity	350 lbs	160 kg
Overall Width	8 ft	2.44 m
Stowed Length	26 ft 5 in	6.53 m
Stowed Height	8 ft 4 in	2.24 m
Ground Clearance (Axle)	12 in	30 cm
Drive Speed	1 mph	1.6 km/h
Outside Turning Radius	11 ft 8 in	3.56 m
Turret Rotation	360°	
Batteries	48v DC 750 Amp-Hr Battery	
Platform Rotation	180°	
Specifications Subject to Change		



**Image shown with the Soft Touch System option.*

SAFETY

- Explosion Proof
- Class I, Division 1, Group D
- Fully Compliant with the Latest UL 583 Type EX Standard
- ANSI A92.20 & CSA B354.6 Compliant

STANDARD EQUIPMENT

- 60 ft Platform Height
- 66 ft Working Height
- 30 x 72 in Platform Size
- 12 in Ground Clearance
- 500 lb Platform Capacity
- Proportional Hydraulic Controls
- Platform Battery Condition Indicator
- Full Height Swing Gate
- Movement Alarm
- 1/2" Airline to Platform

OPTIONS

- Soft Touch System
- Fall Arrest System
- FMR System Fault Monitoring and Recording

