1932EX

Explosion Proof Scissor Lift



Specifications

Working Height	25 ft	7.6 m
Raised Platform Height	19 ft	5.8 m
Lowered Platform Height	42 in	1.1 m
Platform Size (inside)	26 × 64 in	0.7 × 1.6 m
Platform Capacity	550 lbs	250 kg
Overall Width	32 in	0.81 m
Overall Length	89 in	2.26 m
Stowed Height	81.5 in	2.1 m
Deck Extension	3 ft	0.91 m
Ground Clearance (Stowed)	2.375 in	6 cm
Ground Clearance (Raised)	0.7 in	1.8 cm
Wheelbase	55 in	1.4 m
Inside Turning Radius	Zero	
Outside Turning Radius	66 in	1.7 m
Drive Speed (Stowed)	1 mph	1.6 km/h
Drive Speed (Raised)	0.5 mph	0.8 km/h
Batteries	4 × 6V 250 Amp-hr	
Charger	20 Amp Automatic SCR	

^{*}Specifications Subject to Change

Standard Equipment

- 19 ft Platform Height
- · 25 ft Working Height
- 26 x 64 in Platform Size
- 2.375 in Ground Clearance
- 550 lb Platform Capacity
- · 3 ft Extendable Deck

Options

- · Padded Aircraft Rails
- Vertical Access Aid
- Explosion Proof Work Lights
- 1/2" Airline to Platform
 - *May Change Capacity

- · 250 lb Extendable Deck Capacity
- Proportional Drive Controls
- Battery Condition Indicator
- · 250 Amp Hr Battery
- Full Height Swing Gate
- Movement Alarm

Safety

- · Explosion Proof
- · Class I, Division 1, Group D
- Fully Compliant with the Latest UL 583
 Type EX Standard
- ANSI A92.20 & CSA B354.6 Complaint

