2047EX Explosion Proof Scissor Lift



Specifications

Working Height	26 ft	7.9 m
Raised Platform Height	20 ft	6.1 m
Lowered Platform Height	38 in	1.0 m
Platform Size (inside)	42 × 84 in	1.1 × 2.1 m
Platform Capacity	1300 lbs	590 kg
Overall Width	47 in	1.2 m
Overall Length	108 in	2.75 m
Stowed Height	77 in	2.0 m
Deck Extension	4 ft	1.2 m
Ground Clearance (Stowed)	3.5 in	8.9 cm
Ground Clearance (Raised)	0.75 in	1.9 cm
Wheelbase	69 in	1.8 m
Inside Turning Radius	47.5 in	1.2 m
Outside Turning Radius	93.5 in	2.4 m
Drive Speed (Stowed)	1 mph	1.6 km/h
Drive Speed (Raised)	0.5 mph	0.8 km/h
Batteries	4 × 6V 250 Amp-hr	
Charger	20 Amp Automatic SCR	

*Specifications Subject to Change

Standard Equipment

- 20 ft Platform Height
- 26 ft Working Height
- 42 x 84 in Platform Size
- 3.5 in Ground Clearance
- 1300 lb Platform Capacity
- · 34ft Extendable Deck

Options

- Padded Aircraft Rails
- Vertical Access Aid
- Explosion Proof Work Lights
- 1/2" Airline to Platform
 *May Change Capacity

- 300 lb Extendable Deck Capacity
- Proportional Drive Controls
- Battery Condition Indicator
- 250 Amp Hr Battery
- Full Height Swing Gate
- Movement Alarm

Safety

- Explosion Proof
- Class I, Division 1, Group D
- Fully Compliant with the Latest UL 583
 Type EX Standard
- ANSI A92.20 & CSA B354.6 Complaint



baileycranes.com | 262-710-4028 | sales@baileycranes.com