# **Explosion Proof Scissor Lift**



### **Specifications**

Working Height	32 ft	9.8 m
Raised Platform Height	26 ft	7.9 m
Lowered Platform Height	45 in	1.1 m
Platform Size (inside)	42 × 84 in	1.1 × 2.1 m
Platform Capacity	1000 lbs	454 kg
Overall Width	47 in	1.2 m
Overall Length	108 in	2.75 m
Stowed Height	84.5 in	2.1 m
Deck Extension	4 ft	2.1 m
Ground Clearance (Stowed)	3.5 in	8.9 cm
Ground Clearance (Raised)	0.75 in	1.9 cm
Wheelbase	69 in	1.8 m
Inside Turning Radius	47.5in	1.2 m
Outside Turning Radius	93.5 in	2.4 m
Drive Speed (Stowed)	1 mph	1.6 km/h
Drive Speed (Raised)	0.5 mph	0.8 km/h
Batteries	4 × 6V 250 Amp-hr	
Charger	20 Amp Automatic SCR	
Weight (No Options)	6,560 Lbs	

<sup>\*</sup>Specifications Subject to Change

## **Standard Equipment**

- · 26 ft Platform Height
- 32 ft Working Height
- 42 x 84 in Platform Size
- 3.5 in Ground Clearance
- 1000 lb Platform Capacity
- 4 ft Extendable Deck

# **Options**

- · Padded Aircraft Rails
- Vertical Access Aid
- Explosion Proof Work Lights
- 1/2" Airline to Platform
- 6 Foot Powered Extension Deck
  - \*May Change Capacity

- · 300 lb Extendable Deck Capacity
- Proportional Drive Controls
- Battery Condition Indicator
- · 250 Amp Hr Battery
- · Full Height Swing Gate
- Movement Alarm

#### **Safety**

- · Explosion Proof
- · Class I, Division 1, Group D
- Fully Compliant with the Latest UL 583
  Type EX Standard
- · ANSI A92.20 & CSA B354.6 Complaint

