2668EX Explosion Proof Scissor Lift



Specifications

32 ft	9.8 m
26 ft	7.9 m
50 in	1.3 m
57 × 84 in	1.4 × 2.1 m
1,200 lbs	544 kg
68 in	1.7 m
118.5 in	3.01 m
95.5 in	2.4 m
5 ft	1.5 m
7.5 in	19.1 cm
0.7 in	1.8 cm
76 in	1.93 m
76 in	1.93 m
164 in	4.2 m
1 mph	1.6 km/h
0.5 mph	0.8 km/h
	26 ft 50 in 57 × 84 in 1,200 lbs 68 in 118.5 in 95.5 in 5 ft 7.5 in 0.7 in 76 in 76 in 164 in 1 mph

*Specifications Subject to Change

Standard Equipment

- 26 ft Platform Height
- 32 ft Working Height
- 57 x 84 in Platform Size
- 7.5 in Ground Clearance
- 1200 lb Platform Capacity
- 5 ft Extendable Deck

Options

- Padded Aircraft Rails
- Explosion Proof Work Lights
- 1/2" Airline to Platform
 5 ft Powered Extension Deck
- *May Change Capacity

- Proportional Drive Controls
- Proportional Drive Controls
 Battery Condition Indicator
- Full Height Swing Gate
- Movement Alarm

Safety

- Explosion Proof
- Class I, Division 1, Group D
- Fully Compliant with the Latest UL 583 Type EX Standard
- ANSI A92.20 & CSA B354.6 Complaint

