



Specifications

| | | |
|---------------------------|----------------------|-------------|
| Working Height | 36 ft | 11.6 m |
| Raised Platform Height | 32 ft | 9.8 m |
| Lowered Platform Height | 48.5 in | 1.2 m |
| Platform Size (inside) | 42 × 84 in | 1.1 × 2.1 m |
| Platform Capacity | 700 lbs | 318 kg |
| Overall Width | 47 in | 1.2 m |
| Overall Length | 108 in | 2.75 m |
| Stowed Height | 88 in | 2.2 m |
| Deck Extension | 4 ft | 1.2 m |
| Ground Clearance (Stowed) | 3.5 in | 8.9 cm |
| Ground Clearance (Raised) | 0.75 in | 1.9 cm |
| Wheelbase | 69 in | 1.8 m |
| Inside Turning Radius | 47.5 in | 1.2 m |
| Outside Turning Radius | 93.5 in | 2.4 m |
| Drive Speed (Stowed) | 1 mph | 1.6 km/h |
| Drive Speed (Raised) | 0.5 mph | 0.8 km/h |
| Batteries | 4 × 6V 250 Amp-hr | |
| Charger | 20 Amp Automatic SCR | |

*Specifications Subject to Change

Standard Equipment

- 32 ft Platform Height
- 38 ft Working Height
- 42 × 84 in Platform Size
- 3.5 in Ground Clearance
- 700 lb Platform Capacity
- 4 ft Extendable Deck
- 250 lb Extendable Deck Capacity
- Proportional Drive Controls
- Battery Condition Indicator
- 250 Amp Hr Battery
- Full Height Swing Gate
- Movement Alarm

Options

- Padded Aircraft Rails
- Vertical Access Aid
- Explosion Proof Work Lights
- 1/2" Airline to Platform

*May Change Capacity

Safety

- Explosion Proof
- Class I, Division 1, Group D
- Fully Compliant with the Latest UL 583 Type EX Standard
- ANSI A92.20 & CSA B354.6 Complaint

