3268EX

Explosion Proof Scissor Lift



Specifications

| 38 ft | 11.6 m |
|-------------|--|
| 32 ft | 9.8 m |
| 54 in | 1.37 m |
| 56× 96 in | 1.4 × 2.44 m |
| 1,000 lbs | 454 kg |
| 69.5 in | 1.76 m |
| 107 in | 2.72 m |
| 99 in | 2.51 m |
| 69 in | 1.75 m |
| 5 ft | 1.52 m |
| 8 in | 0.20 m |
| Full Height | |
| 80.5 in | 2.04 m |
| 60 in | 1.52 m |
| 156 in | 3.96 m |
| 3.8 mph | 6.1 km/h |
| 0.5 mph | 0.8 km/h |
| | 32 ft 54 in 56× 96 in 1,000 lbs 69.5 in 107 in 99 in 69 in 5 ft 8 in Full Hei 80.5 in 60 in 156 in 3.8 mph |

^{*}Specifications Subject to Change

Standard Equipment

- · 32 ft Platform Height
- 38ft Working Height
- 56 x 96 in Platform Size
- · 8 in Ground Clearance
- 1000 lb Platform Capacity
- 5 ft Extendable Deck

Options

- Padded Aircraft Rails
- Explosion Proof Work Lights
- 1/2" Airline to Platform
- *May Change Capacity

- Proportional Drive Controls
- Battery Condition Indicator
- Full Height Swing Gate
- Movement Alarm

Safety

- · Explosion Proof
- Class I, Division 1, Group D
- Fully Compliant with the Latest UL 583
 Type EX Standard
- · ANSI A92.20 & CSA B354.6 Complaint

