3392EX **Explosion Proof Scissor Lift**



Specifications

| Working Height | 39 ft | 11.89 m |
|----------------------------|-------------------|--------------|
| Raised Platform Height | 33 ft | 10.06 m |
| Lowered Platform Height | 67 in | 1.70 m |
| Platform Size (inside) | 71.7 × 17.7 in | 1.82 × 4.4 m |
| Platform Capacity | 2,750 lbs | 1,247 kg |
| Overall Width | 90.6 in | 2.3 m |
| Overall Length | 177 in | 4.5 m |
| Stowed Height (Rails Up) | 110.5 in | 2.81 m |
| Stowed Height (Rails Down) | 75 in | 1.91 m |
| Deck Extension | 5 ft | 1.5 m |
| Ground Clearance | 10 in | 26 cm |
| Wheelbase | 119 in | 3.0 m |
| Inside Turning Radius | 131 in | 3.33 m |
| Drive Speed (Stowed) | 3.5 mph | 5.6 km/h |
| Drive Speed (Raised) | 0.6 mph | 1 km/h |
| Batteries | 8 × 6V 420 Amp-hr | |
| Charger | Automatic SCR | |

*Specifications Subject to Change

Standard Equipment

- 33 ft Platform Height
- 39 ft Working Height
- 72 x 172 in Platform Size
- 10 in Ground Clearance
- 2,750 lb Platform Capacity
- 5 ft Extendable Deck

Options

- Padded Aircraft Rails
- Explosion Proof Work Lights
- 1/2" Airline to Platform
- 5 ft Powered Extension Deck • Dual 5 ft Roll-out or Powered
- Extendable Decks
- Remote Mount 600 Amp Charger & Battery
- Lithium Ion Battery *May Change Capacity

- 500 lb Extendable Deck Capacity
- Proportional Drive Controls
- Battery Condition Indicator
- Full Height Swing Gate
- Movement Alarm

- Fully Compliant with the Latest UL 583 Type EX Standard
- · ANSI A92.20 & CSA B354.6 Complaint



baileycranes.com I 262-710-4028 I sales@baileycranes.com

- Safety
 - Explosion Proof
 - Class I, Division 1, Group D