### 5392EX

## **Explosion Proof Scissor Lift**



#### **Specifications**

	Ī	
Working Height	59 ft	17.98 m
Raised Platform Height	53 ft	16.15 m
Lowered Platform Height	83.5 in	2.12 m
Platform Size (inside)	71.7 × 71.7 in	1.82 × 4.4 m
Platform Capacity	1,500 lbs	680 kg
Overall Width	90.6 in	2.3 m
Overall Length	177 in	4.5 m
Stowed Height (Rails Up)	126 in	3.2 m
Stowed Height (Rails Down	95.7 in	2.43 m
Deck Extension	5 ft	1.5 m
Ground Clearance	10 in	26 cm
Wheelbase	119 in	3.0 m
Inside Turning Radius	131 in	3.33 in
Drive Speed (Stowed)	3.5 mph	5.6 km/h
Drive Speed (Raised)	0.6 mph	1 km/h
Batteries	8 × 6V 420 Amp-hr	
Charger	Automatic SCR	

<sup>\*</sup>Specifications Subject to Change

# Standard Equipment

- · 53 ft Platform Height
- 59 ft Working Height
- 72 x 21 in Platform Size
- 10 in Ground Clearance
- 1,500 lb Platform Capacity
- 5 ft Extendable Deck

- 500 lb Extendable Deck Capacity
- · Proportional Drive Controls
- Battery Condition Indicator
- · 250 Amp Hr Battery
- Full Height Swing Gate
- Movement Alarm

### **Options**

- · Padded Aircraft Rails
- · Enhanced Padded Aircraft Rails
- Explosion Proof Work Lights
- 1/2" Airline to Platform
- 5 ft Powered Extension Deck
- Dual 5 ft Roll-out or Powered Extendable Decks
- · Remote Mount 600 Amp Charger & Battery
- · Lithium Ion Battery
- FMR System Fault Monitoring and Recording
  \*May Change Capacity

### **Safety**

- Explosion Proof
- · Class I, Division 1, Group D
- Fully Compliant with the Latest UL 583
  Type EX Standard
- · ANSI A92.20 & CSA B354.6 Complaint

