# **AE45JEX**

## **Explosion proof Articulating Boom Lift**



## **Specifications**

51 ft	15.54 m
45 ft	13.72 m
25 ft 2 in	7.67 m
30 × 72 in	.76 × 1.83 m
500 lbs	227 Kg
6 ft 6 in	1. 98 m
21 ft 5 in	6.53 m
7 ft 5 in	2.24 m
145° (+78, -70) vertical ft 8 in	
4 ft 1 in	1.24 m
14 in	36 cm
Zero	
14 ft	4.27 m
1 mph	1.6 km/h
048୩୭୯ 600 Amp-Hr Batter	y1.1 mph
108°	
	45 ft 25 ft 2 in 30 × 72 in 500 lbs 6 ft 6 in 21 ft 5 in 7 ft 5 in 145° (+78, -70) vertical ft 8 i 4 ft 1 in 14 in Zero 14 ft 1 mph 048mplc 600 Amp-Hr Batter

<sup>\*</sup>Specifications Subject to Change

# Standard Equipment

- 60 ft Platform Height
- · 66 ft Working Height
- · 36 x 96 in Platform Size
- 12 in Ground Clearance
- Proportional Hydraulic Controls
- · Platform Battery Condition Indicator
- Full Height Swing Gate
- Movement Alarm
- Movement Alarm
- 1/2' Airline to Platform

### **Options**

- Soft Touch System
- · Fall Arrest System
- FMR System Fault Monitoring and Recording
- \*May Change Capacity

### **Safety**

- Explosion Proof
- · Class I, Division 1, Group D
- Fully Compliant with the Latest UL 583 Type EX Standard
- · ANSI A92.20 & CSA B354.6 Complaint

