MVL15EX

Explosion proof Vertical Mast Lift



Specifications

| Working Height | 20 ft | 6.1 m |
|---------------------------|------------|---------------|
| Raised Platform Height | 15 ft | 6.1 m |
| Platform Size | 26 × 28 in | 0.66 × 0.71 m |
| Platform Capacity | 500 lbs | 227 kg |
| Overall Width | 30 in | 0.76 m |
| Overall Length | 82 in | 2.08 m |
| Stowed Height | 64.75 in | 1.64 m |
| Ground Clearance (Stowed) | 2.1 in | 5.33 cm |
| Ground Clearance (Raised) | 0.63 in | 1.60 cm |
| Inside Turning Radius | Zero | |
| Outside Turning Radius | 55 in | 1.40 m |
| Drive Speed (Stowed) | 1 mph | 1.6 km/h |
| Drive Speed (Raised) | 0.7 mph | 1.1 km/h |

^{*}Specifications Subject to Change

Standard Equipment

- 15 ft 7 in Platform Height
- 21 ft 7 Working Height
- 29 x 41 in Platform Size
- 2.1 in Ground Clearance
- · 500 lb Platform Capacity
- Proportional Drive Controls
- · Battery Condition Indicator
- · 250AMp Hr Battery
- Movement Alarm
- 1/2' Airline to Platform

Options

- · Flashing Amber Beacon
- · Saloon Style Gate
- Fall Arrest System

Safety

- Explosion Proof
- · Class I, Division 1, Group D
- Fully Compliant with the Latest UL 583 Type
 EX Standard
- ANSI A92.20 & CSA B354.6 Complaint

