MVL20EX

Explosion proof Vertical Mast Lift



Specifications

Working Height	25 ft	7.62 m
Raised Platform Height	20 ft	6.1 m
Maximum Drive Height	15 ft 7 in	4.75 m
Platform Size	26 × 28 in	0.66 × 0.71 m
Platform Capacity	350 lbs	160 kg
Overall Width	30 in	0.76 m
Overall Length	82 in	2.08 m
Stowed Height	64.75 in	1.64 m
Ground Clearance (Stowed)	2.1 in	5.33 cm
Ground Clearance (Raised)	0.63 in	1.60 cm
Inside Turning Radius	Zero	
Outside Turning Radius	55 in	1.40 m
Drive Speed (Stowed)	1 mph	1.6 km/h
Drive Speed (Raised)	0.7 mph	1.1 km/h

^{*}Specifications Subject to Change

Standard Equipment

- 15 ft 7 in Platform Height
- · 21 ft 7 Working Height
- 29 x 41 in Platform Size
- 2.1 in Ground Clearance
- 500 lb Platform Capacity
- Proportional Drive Controls
- Battery Condition Indicator
- 250AMp Hr Battery
- Movement Alarm
- 1/2' Airline to Platform

Options

- · Flashing Amber Beacon
- · Saloon Style Gate
- Fall Arrest System

Safety

- Explosion Proof
- · Class I, Division 1, Group D
- Fully Compliant with the Latest UL 583 Type
 EX Standard
- ANSI A92.20 & CSA B354.6 Complaint

